

Specifications Philips LED Panel TrueLine RC530B 34W 5000lm - 940 Cool White | 150x7.5cm - UGR <19 - Dali Dimmable - Best Colour Rendering



[View Product](#)

General Information

| | |
|--------------------------|---|
| SKU | 237451 |
| EAN | 8718699964177 |
| Brand | Philips |
| Manufacturer Name | RC530B LED50S/940 PSD W8L150 VPC PI5 IP |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |
| Series | Panel Led |

Technical Information

| | |
|-----------------------------|--------------------|
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable with Dali |
| Colour Code | 940 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 90-99 |
| Colour of Light | White |
| Light colour options | Single Color |
| Luminous Efficacy (lm/W) | 147.1 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |

| | |
|-----------------------|-------------------------------|
| Fixture Connection | PI [Push-in connector 3-pole] |
| Driver Included | Yes |
| Power factor | >0.90 |
| Product Type Category | LED Panel |

Fixture Information

| | |
|-----------------------|--------------------------------|
| Mounting Method | Recessed |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Operating Temperature | +10 to +40 |
| Emergency Lighting | No Emergency Unit |
| Colour of the Fixture | Aluminium |
| Housing | Steel |
| Colour of material | Aluminium |

Dimensions

| | |
|----------------|-----------|
| LED panel size | 150x7.5cm |
| Length (mm) | 1497 |
| Width (mm) | 75 |
| Height (mm) | 90 |

Sensor Information

Type of sensor

Why Any-lamp?

No Sensor



Order from the **largest lighting specialist** in Europe



Customised quotation



Up to **7 years warranty**



Easy return process